Optimization of Structural and Operational Safety of Helicopters in Ditching

Jan Raphael Kubicek

Department of Aeronautical Engineering, Instituto Federal de São Paulo – Campus São Carlos, São Carlos, São Paulo, Brasil.
Email: jan.raphael.kubicek@ifsp.edu.br .

Abstract – Helicopter ditching in aquatic environments poses critical challenges to operational safety, particularly in emergency situations, due to the medium's complexity and the urgent need for evacuation. This study investigates strategies to optimize both structural and operational safety during ditching, focusing on fuselage strength, hydrodynamic stability, and the effectiveness of evacuation protocols. To achieve this goal, a systematic literature review was conducted, covering scientific articles, technical reports, and experimental studies published between 2000 and 2024. The research analysed various approaches, including the implementation of inflatable buoy configurations and the use of materials with high energy absorption capacity, which are proposed to enhance aircraft crashworthiness. The analysis also considered the integration of emergency flotation systems (EFS) with automated sensors capable of detecting immersion and instantly triggering anti-tipping mechanisms, thereby maintaining aircraft stability and facilitating occupant evacuation. Moreover, the study compares the results obtained from simulations and experimental tests, highlighting the advantages and limitations of conventional approaches versus innovative proposals. The improvements in structural design aim not only to reduce the risk of capsizing and minimize the impacts transmitted to occupants, but also to align new designs with the rigorous standards set by aeronautical authorities such as the Federal Aviation Administration (FAA) and the European Union Aviation Safety Agency (EASA). The recommendations presented herein provide guidelines for the development of more efficient flotation systems and adaptive crashworthy substructures, contributing to a reduction in fatalities and material damage in ditching scenarios. Ultimately, the implementation of these strategies could significantly enhance helicopter safety in emergency situations, promoting important advances in the aeronautical industry.

Keywords: Helicopter ditching; Operational safety; Inflatable buoys; Emergency protocols; Aircraft accidents on water.

1. Introduction

Helicopter ditching, whether in planned operations or emergencies, poses complex challenges to both the operational and structural safety of aircraft. In ditching scenarios, the interaction between the aircraft and the aquatic environment demands solutions that ensure efficient absorption of impact energy, maintain hydrodynamic stability, and enable rapid evacuation of occupants. Recent data indicate that the high incidence of capsizing and the failures of conventional systems have contributed to elevated rates of fatalities and material damage, thereby reinforcing the need for innovations in structural design and the implementation of emergency flotation systems (EFS).

Problem and Objectives:

Despite technological advancements, current solutions often fail to balance safety, stability, and operational performance effectively. Thus, this study aims to address the following question:

How can the structural and operational safety of helicopters during ditching be optimized to minimize the risk of capsizing and enhance the effectiveness of impact absorption systems?

To achieve this, a systematic literature review was conducted to analyze and compare the results of experimental studies and simulations involving different configurations of inflatable floats, crashworthiness mechanisms, and post-impact stability assessments. Additionally, the practical implications of the findings for the aviation industry will be discussed, and guidelines for future research will be proposed.

2. Theoretical Foundation

Forced water landing, or ditching, is a high-risk

event that demands an integrated approach to preserve the aircraft's structural integrity and ensure the survival of its occupants. In this section, the main concepts and recent advances are presented, along with a critical analysis of the gaps in the literature.

2.1 Crashworthiness and Energy Absorption

Controlled impact energy absorption is essential for reducing injuries. According to the report by [1], a crashworthy design should include mechanisms that allow for programmed deformations, keeping the fuselage intact and minimizing load peaks. [2] highlight the importance of innovative structures such as honeycomb panels, collapsible tubes, and reinforced subfloor components, which enhance energy dissipation capacity without exceeding occupant tolerance limits.

In parallel, Figure 1 presents the force versus displacement curve for water impact, illustrating the structural behavior during energy absorption. This is fundamental for validating theoretical crashworthiness models.



Figure 1 – Force (N) vs. Displacement (m) Curve for Water Impact [4]

2.2 Emergency Flotation Systems (EFS)

The EFS are critical for keeping the helicopter stable in the water after impact, enabling a safe evacuation. [3] shows that the proper implementation of EFS can significantly reduce the risk of overturning, while studies by [8] and [9] highlight the importance of optimizing sensors and anti-tipping design for a quick and effective response.

The hydrodynamic analyses were deepened through the stability curves presented in Figures 2 and 3.



Figure 2 – Stability curve with two 1000L upper floats: Shows how the configuration with two upper floats improves the aircraft's stability. [1]



Figure 3 – Stability curves with a 1500L upper float: Highlights the variations in force distribution when using a single float with greater capacity. [1]

2.3 Innovations in Structural Design

New structural design concepts have been proposed to improve impact absorption. [4] developed an innovative substructure concept capable of adapting its response to different types of impacts (water versus rigid surfaces). Experimental studies, such as those by [5], validated the feasibility of these approaches through full-scale tests, demonstrating the reduction of loads transmitted to the occupants.

2.4 Experimental Approaches and Monitoring Techniques

The use of advanced techniques, such as high-speed tracking [6], has enabled the collection of essential dynamic data for the validation of theoretical models. The Technical Report NLR-TP-2002-110 [7] also provides a robust foundation for defining performance standards, contributing to the understanding of energy absorption mechanisms and stability in landing scenarios.

2.5 Synthesis and Perspectives

The integration of advances in crashworthiness, flotation systems, and structural design highlights the need for a multidisciplinary approach. Although there are several isolated studies, consolidating this knowledge through experimental tests and comparative analyses is vital to develop solutions that meet regulatory and operational standards. In this perspective, the present review guides efforts to enhance helicopter safety during water landings and identify directions for future research.

3. Materials and Methods

This study used a systematic literature review, adopting rigorous procedures for the selection, analysis, and comparison of relevant studies on the structural and operational safety of helicopters during water landings.

3.1 Materials

Selected Sources

- Scientific articles and technical reports addressing crashworthiness, EFS, hydrodynamic stability, and structural resistance during water landings were included. The sources were extracted from peer-reviewed journals, international conferences, and regulatory documents, such as the report from [1].

Inclusion and Exclusion Criteria

  - Inclusão: Estudos publicados entre 2000 e 2024, com dados experimentais ou simulações detalhadas sobre a segurança estrutural e os sistemas de flutuação.
  - Exclusão: Artigos sem descrição detalhada dos métodos ou com dados incompletos.

Bases de Dados e Palavras-Chave

- A busca foi realizada em Scopus, ScienceDirect, IEEE Xplore e Google Scholar, utilizando termos como "helicopter ditching", "crashworthiness", "emergency flotation system", "water impact simulation" e "hydrodynamic stability".

.

3.2 Methods

Literature Review

- The selection of articles followed the PRISMA protocol, ensuring transparency and rigor in the study selection process. Each article was analyzed in terms of objectives, methodology, results, and conclusions, allowing for a comparative synthesis of the findings.

Comparative Analysis and Data Synthesis

- The results regarding the efficiency of EFS, energy absorption capacity, and post-impact stability were compared. A summary table (Table 1) was created to synthesize the main data from the reviewed studies, facilitating the visualization of similarities, discrepancies, and gaps.

Assessment of Risk Analysis Methods

- Studies that used methods such as FMEA and QRA were included to identify vulnerabilities in water landing scenarios, allowing for the extraction of recommendations for risk mitigation.

Development of Guidelines

Based on the comparative analysis of the data, guidelines for improving safety were formulated, aligned with current regulatory standards. These guidelines were structured to be applicable in industrial practice and to guide future research.

3.3 Methodological Considerations

Although this study did not conduct direct experiments or simulations, the critical analysis of data from the reviewed studies allowed for the identification of patterns and trends that elucidate the main challenges and solutions in helicopter water landings.

4. Results and Discussion

The analysis of the reviewed studies demonstrated that optimizing safety during water landings relies on the integration of structural and operational strategies, as well as the incorporation of advanced technologies.

4.1 Structural Safety and Energy Absorption

"Studies by [2] indicate that the use of structures such as honeycomb and collapsible tubes significantly increases energy absorption capacity, which is essential for a crashworthy design. However, [4] emphasize that, in water impacts, conventional structures may not absorb energy effectively due to the lower resistance of the aquatic medium. The comparison suggests that an adaptive substructure, which modulates its response according to the type of impact, could reduce the loads transmitted to the occupants.

Table 1 – Comparison of Key Crashworthiness

Indicators

Study	Material/Structure	Energy Absorption Indicator	Observations
Yang et al. (2020)	Honeycomb, tubes	High	Planned deformation, minimized peaks
Vignjevic & Meo (2002)	Conventional Substructure	Moderate/Lower	Less effective water impact

Figure 4 illustrates the collision responses of a helicopter in free fall:



(a) Attitude sequences of a helicopter ditching with an incident angle of 6 degrees [248].

(b) Falling wave velocity contours of a helicopter ditching with a pitching angle of 10 degrees [250].

Figure 4(a): Attitude sequences during a forced landing with an incidence angle of 6° [2].

Figure 4(b): Fall wave velocity contours with a tilt angle of 10°.

Additionally, the analysis of Figure 4 (previously presented) reinforces the understanding of the fuselage behavior through the force versus displacement curve for water impact, highlighting the importance of a design that maximizes energy absorption without compromising structural integrity.

4.2 Emergency Flotation Systems (EFS) and Hydrodynamic Stability

Recent studies ([3]; [8]; [9]) highlight that the effectiveness of EFS is directly related to the distribution, volume of the floats, and activation speed. The integration of automated sensors, as suggested by [8], can ensure an immediate response, reducing the risk of overturning and keeping the aircraft leveled.

As demonstrated by Figures 1 and 2:

Figure 2 – Stability curve with two 1000L upper floats: Indicates the improvement in stability provided by a configuration with two floats.

Figure 3 – Stability curves with a 1500L upper float: Highlights the variations in static response when using a float with greater capacity.

These advances enable a safe and effective evacuation of the occupants, even considering changes in mass distribution and the center of gravity.

4.3 Impact of Flotation Systems on Operational Performance

The implementation of EFS, while crucial for safety, can alter the mass distribution and the helicopter's center of gravity. [5] demonstrated that, if not properly sized, the floats can compromise post-impact stability and affect the aircraft's aerodynamic performance. This aspect emphasizes the need for a design that balances the benefits of flotation systems with operational requirements, without compromising overall performance.

4.4 Emergency Procedures and Crew Training

The evacuation of occupants depends not only on the physical design of the aircraft but also on the effectiveness of emergency protocols. [6] highlight that 'lateral flotation,' keeping part of the cabin above water, facilitates evacuation, but only if accompanied by specific training and standardized operational protocols. The report from [1] reinforces the importance of regular training to minimize disorientation and increase evacuation efficiency.

4.5 Integration with Regulations and Recommendations

Despite technological advances, many of the proposed systems are still not fully integrated into regulatory standards. It is recommended:

- Review of post-impact stability criteria: Adjust parameters to reduce the risk of overturning.
- Full-scale experimental tests: Validate models and simulations with data obtained under operational conditions.

- Implementation of automated sensors: Minimize reliance on manual intervention for EFS activation.

4.6 Summary of Results

The optimization of safety in ditching requires the integration of four key elements:

- **Improvement of Crashworthiness:** Use of substructures that efficiently absorb impact energy**.**
- **Enhancement of EFS:** Design and rapid activation of inflatable floats**.**
- **Technological Integration:** Use of sensors and automated systems for immediate response.
- **Operational Training:** Well-defined emergency protocols and continuous crew training.

These strategies, when combined, can significantly reduce risks and raise safety standards in helicopter operations in aquatic environments.

5. Conclusion

The structural and operational safety of helicopters during ditching is a challenge that requires innovative and integrated solutions. The systematic review conducted highlights significant advances in energy absorption and flotation systems; however, challenges remain, particularly in post-impact stability and the full integration of devices into international regulatory standards.

The results suggest that optimizing floor designs, combined with the implementation of EFS equipped with automated detection technology, can reduce the loads transmitted to occupants and prevent rollovers. Additionally, enhanced operational protocols and specific training are essential for effective evacuation.

Future research should focus on experimental tests at full scale, investigation of new materials with higher energy absorption capacity, and reevaluation of regulatory standards in light of technological advancements. The consolidation of these strategies promises to enhance safety levels in aviation, more effectively protecting occupants in emergency situations.

6. References

[1] EASA. 2007. C16 « Study on Helicopter Ditching and Crashworthiness ».

[2] Yang X, Ma J, Wen D, Yang J. Crashworthy design and energy absorption mechanisms for helicopter structures: A systematic literature review. *J Aerosp Eng*. 2020; 234(4): 451-468.

[3] Aziz A, Mad Sariff E, Shamsudheen I, Abd Jamil R, Abu Zarim M. The effect of emergency flotation system (EFS) on helicopter stability during ditching. *Int J Aeronaut Space Sci*. 2023; 55(3): 120-132.

[4] Vignjevic R, Meo M. A new concept for a helicopter sub-floor structure crashworthy in impacts on water and rigid surfaces. *Int J Crashworthiness*. 2002; 7(2): 215-230.

[5] Pentecôte N, Vigliotti A. Crashworthiness of helicopters on water: Test and simulation of a full-scale WG30 impacting on water. *J Aerosp Eng*. 2003; 36(6): 451-465.

[6] Faiella E, Grizzi S, Passacantilli F, Santic I, Sellini M. Experimental analysis of high-speed tracking during helicopter ditching. *Aeronautical J*. 2024; 123(1): 1-12.

[7] Ubels L, Wiggenraad J. NLR-TP-2002-110: A study on helicopter ditching techniques. *Netherlands Aerospace Centre*. 2002; 110: 1-45.

[8] Wang B, Wang Z, Sun Z, Zhou B. Optimal design of water immersion sensor layout for helicopter emergency flotation system based on the NSGA-II algorithm. *J Adv Aerosp Tech*. 2024; 12(2): 112-123.

[9] Yang L, Huang Y, Sun L, He F, Zhu Y. Test and simulation of emergency flotation system buoy anti-overturning method. *Aerosp Sci Technol*. 2024; 45(3): 233-245.